



# ENTRY/EXIT STATION

Vehicular Access Control Station

ParQube LS is the ideal solution for nested areas control.

Parking  
technology

# HUB



## Base model

- Outdoor housing
- Wall or pole fixing
- Lockable front access door
- Steel sheet structure painted RAL 7021
- Front door painted RAL 9003
- Intercom button & cover
- Electronic control board for communication with central unit by RS485 network or TCP/IP
- Passive proximity reader for cards 125 kHz ISO size
- Heater & fan with built in thermostat

## Options

- Customized color housing
- Backlit LCD display 4 x 20 characters
- Omni-directional laser scanner for tickets
- Active or passive AVI readers
- Analog intercom system
- Intercom over IP

## Standard Features

- Online with central unit
- RS485 communication network as standard or TCP/IP by ETH converter
- Rate changes for transient users by ticket scanning
- Control of all tickets and cards by means of contactless reader
- Two way ticket scanning
- Passive proximity reader for cards 125 kHz ISO size
- Up to 5.000 users storage offline
- Up to 15.000 events storage offline
- Free input for external reader
- Active or passive long range reader (AVI managed by software)
- Antipassback card management online with central unit
- Opening pulse operating against valid ticket or card check
- Function setting by an on board jumper



### Peripheral Dimensions (W x D x H)

300mm x 170mm x 540mm

11,8in x 6,7in x 21,2in

### Power Consumption

60w

### Electrical

115 - 230 VAC, 50-60Hz

### Temperature

-20°C / + 50°C